

Lithium Polymer Battery LP482122 1S1P

Incl. PCB standard (max. discharge current 10C)

in shrink sleeve and wire 100 mm AWG 20 red / black, ends stripped and tinned

Electrical characteristics

Order no. 60.10366

Nominal voltage	3.7 V	
Typical capacity	180 mAh	(0.2C / 3.0 V at 20°C)
Minimum capacity	171 mAh	(0.2C / 3.0 V at 20°C)
Impedance initial	≤200 mΩ	
Max. cont. charge	180 mA	
Max. charge voltage	4.2 V	
Max. cont. discharge	1.5 A	
Pulse Discharge current	1.5 A for 40 S	
Discharge Cut off	3.0 V	
Life expectancy	500 >80 % of initial capacity	0.5C charge / 0.5C Discharge (20°C)
Operating temperature range		
charge	10°C ~ +45°C	10°C ~ +18°C max. 0.5C 18°C ~ +45°C max. 1.0C
discharge	-20°C ~ +60°C	
Storage temperature	0°C ~ +25°C	


PCM data

Overcharge protection	Overcharge detection voltage	4.28 V ±0.025 V (Delay time 1.5 S)
	Overcharge release voltage	4.13 V ±0.05 V
Overdischarge protection	Overdischarge detection voltage	2.8 V ±0.05 V (Delay time 180 mS)
	Overdischarge release voltage	3.1 V ±0.1 V
Overcurrent protection	Overcharge detection current	2.5 – 5 A (Delay time 7.2 – 11 mS)
	Overdischarge detection current	3 – 8 A (Delay time 7.2 – 11 mS)
	Release condition	Cut load
Short protection	Detection condition	Exterior short circuit (Delay time 240 – 360 μS)
	Release condition	Cut short circuit
Continue current	Continuous output discharging current	≤1.5 A
Interior resistance	Main loop electrify resistance (VC = 3.8 V)	≤80 mΩ
Current consumption	Normal mode	≤6.0 μA
The 0 V battery charging function	available / unavailable	available

Physical characteristics

Length	max. 24.5 mm	
Width	max. 22.2 mm	
Thickness	max. 5.0 mm	after cycling +8 %
Weight	4.2 ±0.8 g	

Drawing:



Delivery Status

Battery Voltage	3.7 – 3.9 V
Battery Capacity	tbd

Warning

- n** Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures.
- n** Do not short or install with incorrect polarity.
- n** Replace battery with DYNAMIS Batterien – 60.16728 only. Use of another battery may present a risk of fire or explosion.
- n** Caution – The battery used in this device may present a risk of fire or chemical burn if mistreated.
Do not disassemble, heat above 100°C, or incinerate.
- n** Dispose of used battery promptly. Keep away from children.
Do not disassemble and do not dispose of in fire.
- n** Do not exceed the maximum charging voltages, currents and temperatures listed above.

All information (subject to change without notice) contained in this document is for reference only and should not be used as a basis for product guaranty or warranty. For applications other than those described here, please consult your nearest DYNAMIS Sales or Marketing Office or Distributors.