

Lithium Polymer Battery LP743234 1S1P

Incl. PCM (max. discharge current 1C) and NTC 10 kOhm
with wire 50 mm AWG 24 red / white / black and connector Molex 5040510301

Electrical characteristics

Order no. 60.10376

Nominal voltage	3.85 V	
Typical capacity	1'030 mAh	(0.2C / 3.0 V at 20°C)
Minimum capacity	980 mAh	(0.2C / 3.0 V at 20°C)
Impedance initial	≤150 mΩ	
Max. cont. charge	1'030 mA	Cut-off Current 0.02C
Max. charge voltage	4.4 V	
Max. cont. discharge	1'030 mA	
Discharge Cut off	3.0 V	
Life expectancy	≥500 >80 % of initial capacity	0.5C charge / 0.5C Discharge (20°C)
Operating temperature range		
charge	10°C ~ +45°C	10°C ~ 15°C max. 0.2C 15°C ~ +45°C max. 1C
discharge	-20°C ~ +60°C	
Storage temperature	10°C ~ +25°C	


PCM data

Overcharge protection	Overcharge detection voltage	4.475 V ±0.02 V
	delay time	1.2 mS
	Overcharge release voltage	4.275 V ±0.03 V
Overdischarge protection	Overdischarge detection voltage	2.800 V ±0.05 V
	delay time	172.8 mS
	Overdischarge release voltage	3.0 V ±0.05 V
Overcurrent protection	Overcurrent detection current	4 ~ 10 A
	delay time	9.6 ~ 14.4 mS
	Release condition	Cut load
Short protection	Detection condition	Exterior Short circuit
	delay time	200 ~ 500 uS
	Release condition	Cut short circuit
Continue current	Continuous output discharge current	≤2 A
Interior resistance	Main loop electrify resistance	(VC = 3.8 V) R _{DS} ≤60 mΩ
Current consumption	Normal mode	≤6 0 μA

Cell dimensions

Length	max. 37.0 mm	
Width	max. 32.7 mm	
Thickness	max. 7.5 mm	
Weight	16.4 ±2 g	

Drawing:



Delivery Status

Battery Voltage	3.7 – 3.9 V
Battery Capacity	tbd

Warning

- n** Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures.
- n** Do not short or install with incorrect polarity.
- n** Replace battery with DYNAMIS Batterien – 60.16728 only. Use of another battery may present a risk of fire or explosion.
- n** Caution – The battery used in this device may present a risk of fire or chemical burn if mistreated. Do not disassemble, heat above 100°C, or incinerate.
- n** Dispose of used battery promptly. Keep away from children. Do not disassemble and do not dispose of in fire.
- n** Do not exceed the maximum charging voltages, currents and temperatures listed above.

All information (subject to change without notice) contained in this document is for reference only and should not be used as a basis for product guaranty or warranty. For applications other than those described here, please consult your nearest DYNAMIS Sales or Marketing Office or Distributors.